

MICROPOWER GROUP™

POWERFUL SOLUTIONS PARTNER

## SAME BOX BUT WITH 30% MORE POWER!

Access 130 and Lion 130, 3-phase HF battery chargers optimized for capacities between 10 and 13 kW. The chargers are compact, still powerful, and available for 380-440VAC and 480VAC, secondary voltage from 24V up to 120V. Lion 130 is the model for all lithium-ion applications and Access 130 takes care of lead-acid and virtually any other chemistry. Both models are of course CE and UL certified.

## 100W - 26 kW range of battery chargers

The Access 130 and Lion 130 battery chargers have the same casing as Access 100 and Lion 100 but comes with 30% more power. With future development of double-packs, the Access 130 and Lion 130 will be available up to 26 kW (or higher with multiple assemblies).

## **Compatible with GET**

The Access 130 and Lion 130 are like other chargers compatible with the Micropower GET system. GET gives full control over the fleet wherever you are, optimizes the daily business operations and saves time through simplifying service and maintenance, hence increasing uptime.





Both models are CE and UL certified



Access 130 / Lion 130			
3x380-440 VAC (CE)		3x480 VAC (UL)	
Secondary Voltage (V)	Secondary Current (A)	Secondary Voltage (V)	Secondary Current (A)
24	300		
36	300	36	300
48	220	48	220
80	130	80	130
96	100		
120	90		



Micropower Group AB Gullhallavägen 20, SE-352 50 Växjö, Sweden

Phone: +46 (0)470 727 400 sales@micropower.se www.micropower-group.com